

# SAFETY DATA SHEET

Date Prepared : 09/13/2017  
 MSDS No : SM5514  
 Date Revised : 09/13/2017  
 Revision No : 5

## ACRYL-R SM5514 Low VOC Acrylic Self-Leveling Sealant

### 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** ACRYL-R SM5514 Low VOC Acrylic Self-Leveling Sealant

#### MANUFACTURER

ITW Polymers Sealants North America  
 111 South Nursery Road  
 Irving, TX 75060

**Product Stewardship:** (972) 438-9111

#### 24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (US Transportation): (800) 424-9300

**COMMENTS:** ACRYL-R is a registered trademark of Illinois Tool Works, Inc.

### 2. HAZARDS IDENTIFICATION

#### GHS CLASSIFICATIONS

##### Health:

Skin Irritation, Category 2  
 Reproductive Toxicity, Category 2  
 Target Organ Toxicity (Single exposure), Category 3  
 Target Organ Toxicity (Repeated exposure), Category 2  
 Aspiration Hazard, Category 1

##### Environmental:

Acute Hazards to the Aquatic Environment, Category 2

##### Physical:

Flammable Liquids, Category 2

#### GHS LABEL



Flame



Health  
hazard



Exclamation  
mark

**SIGNAL WORD:** DANGER

#### HAZARD STATEMENTS

H225: Highly flammable liquid and vapour.  
 H304: May be fatal if swallowed and enters airways.  
 H315: Causes skin irritation.  
 H336: May cause drowsiness or dizziness.  
 H361: Suspected of damaging fertility or the unborn child.  
 H373: May cause damage to organs through prolonged or repeated exposure.  
 H401: Toxic to aquatic life.

#### PRECAUTIONARY STATEMENT(S)

##### Prevention:

[201]: Obtain special instructions before use.  
 P202: Do not handle until all safety precautions have been read and understood.

# SAFETY DATA SHEET

Date Prepared : 09/13/2017

MSDS No : SM5514

Date Revised : 09/13/2017

Revision No : 5

## ACRYL-R SM5514 Low VOC Acrylic Self-Leveling Sealant

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P233: Keep container tightly closed.  
 P240: Ground and bond container and receiving equipment.  
 P241: Use explosion-proof [electrical/ventilating/lighting] equipment.  
 P242: Use non-sparking tools.  
 P243: Take action to prevent static discharges.  
 P260: Do not breathe dust/fume/gas/mist/vapours/spray.  
 P264: Wash thoroughly after handling.  
 P271: Use only outdoors or in a well-ventilated area.  
 P273: Avoid release to the environment.  
 P280: Wear protective gloves/protective clothing/eye protection/face protection.

### Response:

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
 P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
 P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P308+P313: IF exposed or concerned: Get medical advice/ attention.  
 P321: Specific treatment is required.  
 P331: Do NOT induce vomiting.  
 P332+P313: If skin irritation occurs: Get medical advice/attention.  
 P362: Take off contaminated clothing.  
 P370+P378: In case of fire: Use appropriate media to extinguish.

### Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.  
 P403+P235: Store in a well-ventilated place. Keep cool.  
 P405: Store locked up.

### Disposal:

P501: Dispose of contents/container according to local, regional, national, and international regulations.

## EMERGENCY OVERVIEW

**IMMEDIATE CONCERNS:** DANGER! Extremely flammable liquid and vapor. Vapor may cause flash fire and explosion. Harmful or fatal if swallowed. Harmful if absorbed through the skin. Pulmonary aspiration hazard. After ingestion, may enter lungs and produce damage. High vapor concentrations may cause drowsiness. Can cause eye, skin and respiratory tract irritation.

## POTENTIAL HEALTH EFFECTS

**EYES:** Can cause moderate to severe eye irritation with temporary damage possible.

**SKIN:** Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

**INGESTION:** Harmful or fatal if swallowed. Can cause gastrointestinal irritation with symptoms of nausea, vomiting and diarrhea.

**INHALATION:** Respiratory tract irritant. High concentrations may cause dizziness, headache, and anesthetic effects.

**ROUTES OF ENTRY:** Eye and Skin Contact, Inhalation and Ingestion

**IRRITANCY:** Eyes, nose, throat, respiratory tract, and skin irritation.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

# SAFETY DATA SHEET

Date Prepared : 09/13/2017

MSDS No : SM5514

Date Revised : 09/13/2017

Revision No : 5

## ACRYL-R SM5514 Low VOC Acrylic Self-Leveling Sealant

Chemical Name	Wt.%	CAS
Dimethyl Carbonate	35 - 45	616-38-6
Toluene	< 3	108-88-3

### 4. FIRST AID MEASURES

**EYES:** Immediately flush eyes with plenty of tempered water (at least 15-20 minutes) lifting upper and lower eye lids occasionally. Get immediate medical attention.

**SKIN:** Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash or dispose of clothing before reuse.

**INGESTION:** Do not induce vomiting, keep person warm, quiet and get medical attention immediately. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Aspiration of this material into the lungs due to vomiting can cause chemical pneumonitis which can be fatal.

**INHALATION:** Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

#### SIGNS AND SYMPTOMS OF OVEREXPOSURE

**EYES:** Liquid and vapor can severely irritate the eyes depending on type of exposure (splash, vapor) and exposure time.

**SKIN:** Mild to moderate skin irritant.

**INGESTION:** May cause vomiting.

**INHALATION:** Respiratory tract irritation. High concentration may cause dizziness, headache, and anesthetic effects.

**ACUTE EFFECTS:** High vapor concentrations may cause central nervous system (CNS) depression with symptoms including light headedness, giddiness, nausea, drowsiness, headache, nose, throat and respiratory tract irritation, reduced appetite, confusion and unconsciousness.

**CHRONIC EFFECTS:** Chronic effects of ingestion and subsequent aspiration into the lungs may cause pneumonitis (lung cavity) formation and chronic lung dysfunction.

Reports have associated repeated or prolonged occupational exposure to solvents with irreversible brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.

**NOTES TO PHYSICIAN:** Treat symptomatically.

### 5. FIRE FIGHTING MEASURES

**FLAMMABLE CLASS:** Class IB

**GENERAL HAZARD:** Flammable liquid and vapor.

**EXTINGUISHING MEDIA:** Use methods appropriate for the surrounding fire. Water spray, dry chemical, carbon dioxide, AFFF or alcohol resistant foams are all appropriate.

**HAZARDOUS COMBUSTION PRODUCTS:** Carbon dioxide, carbon monoxide, smoke, fumes and/or unburned hydrocarbons

**EXPLOSION HAZARDS:** Avoid fire, sparks, static electricity and hot surfaces. Liquid readily evaporates at room/ambient temperature. Vapors are invisible, flammable, heavier than air, and may accumulate in low areas and spread long distances. Distant ignition and flashback are possible.

# SAFETY DATA SHEET

Date Prepared : 09/13/2017

MSDS No : SM5514

Date Revised : 09/13/2017

Revision No : 5

## ACRYL-R SM5514 Low VOC Acrylic Self-Leveling Sealant

**FIRE FIGHTING PROCEDURES:** As in any fire, wear self-contained breathing apparatus with pressure-demand, full face piece SCBA (MSHA/NIOSH approved or equivalent) and full protective gear.

**SENSITIVE TO STATIC DISCHARGE:** Likely to catch fire from near-by spark. Static charge may accumulate by flow or agitation. Grounding and bonding of containers is required.

**SENSITIVITY TO IMPACT:** None known.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon dioxide, carbon monoxide, or hydrocarbon fumes if heated to decomposition.

### 6. ACCIDENTAL RELEASE MEASURES

**SMALL SPILL:** Dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material on absorbent, such as sawdust or vermiculite, and sweep into closed containers for disposal. After all visible traces, including ignitable vapors, have been removed, thoroughly wet vacuum the area. Do not flush to sewer. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for disposal. Only those persons who are adequately trained, authorized, and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up.

**LARGE SPILL:** Keep spectators away. Only those persons who are adequately trained, authorized and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up. Ventilate the area by natural means or by explosion proof mechanical means (i.e. fans). Know and prepare for spill response before using or handling this product. Eliminate all ignition sources (flames, hot surfaces, portable heaters and sources of electrical, static, or frictional sparks). Dike and contain spill with inert material (e.g. sand, earth). Transfer liquids to covered and labeled metal containers for recovery or disposal, or remove with inert absorbent. Use only non-sparking tools and appropriate PPE. Place absorbent diking materials in covered metal containers for disposal. Prevent contamination of sewers, streams, and groundwater with spilled material or used absorbent.

### ENVIRONMENTAL PRECAUTIONS

**WATER SPILL:** Avoid run-off into storm drains, ditches and waterways.

### 7. HANDLING AND STORAGE

**GENERAL PROCEDURES:** For professional or industrial use only. Follow label instructions. Keep out of the reach of children. Not for consumption. No smoking. Do not breathe vapors. Avoid contact with body. Turn off all pilot lights, flames, stoves, heaters, electric motors, welding equipment and other sources of ignition. Empty containers must not be washed and re-used for any purpose. Contact lens wearers must wear protective eye wear around chemical vapors and liquid. Wash hands thoroughly after handling. Flammable vapors may cause flash fire or ignite explosively. To prevent build-up of vapors, use adequate natural and/or mechanical ventilation (e.g. open all windows and doors to achieve cross ventilation). Containers may be hazardous when empty. Never use welding or cutting torch on or near container. Do not cut, drill, grind, or expose containers to heat, sparks, static electricity or other source of ignition. Explosion may occur causing injury or death.

**HANDLING:** Use adequate ventilation and appropriate respiratory protection to avoid breathing vapors when cover is removed. Ground and bond all equipment when handling flammable solvent-borne material.

**STORAGE:** Keep container closed when not in use. Store in a dry well ventilated area, out of the sun and away from ignition sources. Do not remove or deface label. Prevent water or moist air from entering container. Do not store in the same area with alcohols, amines, strong bases and surface active materials.

**SHELF LIFE:** 18 months from manufacture date @ 80 F ( 26.7 C)

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

# SAFETY DATA SHEET

Date Prepared : 09/13/2017

MSDS No : SM5514

Date Revised : 09/13/2017

Revision No : 5

## ACRYL-R SM5514 Low VOC Acrylic Self-Leveling Sealant

### EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)				
EXPOSURE LIMITS				
Chemical Name	Type		ppm	mg/m <sup>3</sup>
Dimethyl Carbonate	OSHA PEL	TWA	NL [1]	NL [1]
		STEL	NL [1]	NL [1]
	ACGIH TLV	TWA	NL [1]	NL [1]
		STEL	NL [1]	NL [1]
Toluene	OSHA PEL	TWA	200 ppm	NL
		STEL	300 ppm [2]	NL [2]
	ACGIH TLV	TWA	20 ppm	NL
		STEL	NL [1]	NL [1]

**Footnotes:**  
 1. NL = Not Listed  
 2. C = Ceiling

**ENGINEERING CONTROLS:** Provide sufficient explosion proof mechanical (general and/or local exhaust) ventilation to maintain exposure below the occupational exposure limit and exposure concentration.

### PERSONAL PROTECTIVE EQUIPMENT

**EYES AND FACE:** Wear safety glasses with side shields (or goggles) or a full face respirator.

**SKIN:** Wear chemical protective clothing & boots to prevent repeated or prolonged skin contact. Wear impervious gloves, if needed, to prevent repeated or prolonged skin contact.

**RESPIRATORY:** NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

**PROTECTIVE CLOTHING:** Wear chemical resistant gloves, such as nitrile rubber.

**WORK HYGIENIC PRACTICES:** Use good hygiene practices when handling this material. Wash hands thoroughly after use.

**OTHER USE PRECAUTIONS:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

**PHYSICAL STATE:** Viscous Liquid

**ODOR:** Slight Aromatic Odor

**ODOR THRESHOLD:** Not Determined

**COLOR:** Various

# SAFETY DATA SHEET

Date Prepared : 09/13/2017

MSDS No : SM5514

Date Revised : 09/13/2017

Revision No : 5

## ACRYL-R SM5514 Low VOC Acrylic Self-Leveling Sealant

**pH:** 7.02**PERCENT VOLATILE:** 39.7**Notes:** by weight**FLASHPOINT AND METHOD:** 17°C (63°F)**FLAMMABLE LIMITS:** 4.2 to 12.9**Notes:** (dimethyl carbonate)**AUTOIGNITION TEMPERATURE:** 465°C (869°F)**Notes:** (dimethyl carbonate)**VAPOR PRESSURE:** 5.6 kPa at 20°C**VAPOR DENSITY:** 3.1**BOILING POINT:** Not Determined**FREEZING POINT:** Not Determined**MELTING POINT:** Not Determined**POUR POINT:** Not Determined**SOLUBILITY IN WATER:** Nonsoluble**PARTITION COEFFICIENT: N-OCTANOL/WATER:** Not Determined**DENSITY:** 9.45 lbs/gal**SPECIFIC GRAVITY:** 1.133**VISCOSITY:** Not Determined**(VOC):** 62 gr/L EPA Method 24 (where DMC is approved as exempt compound)**OXIDIZING PROPERTIES:** Not Determined**COMMENTS:** 479.3 gr/L EPA Method 24 (where DMC is a VOC)

### 10. STABILITY AND REACTIVITY

**REACTIVITY:** Yes**HAZARDOUS POLYMERIZATION:** Product will not undergo polymerization.**STABILITY:** Stable.**CONDITIONS TO AVOID:** Avoid heat, flames, sparks, and other sources of ignition. Keep away from strong oxidizing conditions and agents.**POSSIBILITY OF HAZARDOUS REACTIONS:** None Expected.**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide, carbon dioxide and hydrocarbon fumes if heated to decomposition.**INCOMPATIBLE MATERIALS:** Strong oxidizing agents and amines.

### 11. TOXICOLOGICAL INFORMATION

#### ACUTE TOXICITY

# SAFETY DATA SHEET

Date Prepared : 09/13/2017  
 MSDS No : SM5514  
 Date Revised : 09/13/2017  
 Revision No : 5

## ACRYL-R SM5514 Low VOC Acrylic Self-Leveling Sealant

Chemical Name	ORAL LD <sub>50</sub> (rat)	DERMAL LD <sub>50</sub> (rabbit)	INHALATION LC <sub>50</sub> (rat)
Dimethyl Carbonate	6000 mg/kg (mouse)	5000 mg/kg (rabbits)	No data
Toluene	2600 to 7500 mg/kg	12124 mg/kg	8000 ppm (4-hr dose)

**SERIOUS EYE DAMAGE/IRRITATION:** Eyes, nose, throat, respiratory tract irritation.

### CARCINOGENICITY

Chemical Name	IARC Status
Toluene	3

## 12. ECOLOGICAL INFORMATION

**ENVIRONMENTAL DATA:** This product contains components that will normally float on water. These components may be harmful to aquatic organisms and may cause long term adverse effects in the aquatic environment.

**ECOTOXICOLOGICAL INFORMATION:** Contains components that are potentially toxic to freshwater and saltwater ecosystems.

**BIOACCUMULATION/ACCUMULATION:** Contains components with the potential to bio-accumulate.

## 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** Dispose of in accordance with all local, state and federal regulations.

## 14. TRANSPORT INFORMATION

### DOT (DEPARTMENT OF TRANSPORTATION)

**PROPER SHIPPING NAME:** Flammable Liquid, N.O.S.

**TECHNICAL NAME:** contains (Dimethyl Carbonate)

**PRIMARY HAZARD CLASS/DIVISION:** 3

**UN/NA NUMBER:** 1993

**PACKING GROUP:** II

**NAERG:** 128

**MARINE POLLUTANT #1:** None

## 15. REGULATORY INFORMATION

### UNITED STATES

#### DOT LABEL SYMBOL AND HAZARD CLASSIFICATION



Flammable  
Liquid

### SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

**FIRE:** Yes **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** Yes

# SAFETY DATA SHEET

**Date Prepared :** 09/13/2017  
**MSDS No :** SM5514  
**Date Revised :** 09/13/2017  
**Revision No :** 5

## ACRYL-R SM5514 Low VOC Acrylic Self-Leveling Sealant

### EPCRA SECTION 313 SUPPLIER NOTIFICATION

Chemical Name	Wt.%	CAS
Toluene	< 3	108-88-3

### CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

Chemical Name	Wt.%	CERCLA RQ
Toluene	< 3	1,000 lbs.

### TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Dimethyl Carbonate	616-38-6
Toluene	108-88-3

### CLEAN AIR ACT

Chemical Name	Wt.%	CAS
Toluene	< 3	108-88-3

### STATES WITH SPECIAL REQUIREMENTS

Chemical Name	Requirements
Dimethyl Carbonate	Pennsylvania Right to Know List Massachusetts Right to Know List New Jersey Right to Know List Connecticut Hazardous Material Survey
Toluene	New Jersey Right to Know List Pennsylvania Right to Know List Massachusetts Toxic Use Reduction Act (TURA) Reportable Chemical

**CALIFORNIA PROPOSITION 65:** This product contains toluene, a chemical known to the state of California to cause birth defects or other reproductive harm.

Chemical Name	Wt.%	Listed
Toluene	< 3	Developmental Toxicity

### CANADA

#### WHMIS HAZARD SYMBOL AND CLASSIFICATION



Flammable  
Liquid



Toxic

### 16. OTHER INFORMATION

**Date Revised:** 09/13/2017



# SAFETY DATA SHEET

Date Prepared : 09/13/2017  
 MSDS No : SM5514  
 Date Revised : 09/13/2017  
 Revision No : 5

## ACRYL-R SM5514 Low VOC Acrylic Self-Leveling Sealant


**INFORMATION CONTACT:** (972) 438-9111

**REVISION SUMMARY:** This MSDS replaces the 12/09/2015 MSDS. Revised: **Section 1:** Date Issued.

### HMIS RATING

<b>HEALTH</b>	*	<b>2</b>
<b>FLAMMABILITY</b>		<b>3</b>
<b>PHYSICAL HAZARD</b>		<b>0</b>
<b>PERSONAL PROTECTION</b>		<b>B</b>

### NFPA CODES



**GENERAL STATEMENTS:** Keep out of reach of children  
 For professional or industrial use only

**MANUFACTURER DISCLAIMER:** This document may be used to comply with OSHA's Hazardous Communication Standard, 29 CFR 1910.1200.

To the best of our knowledge, the information contained in this SDS is accurate. It is intended to assist the user in his/her evaluation of the product's hazards and safety precautions to be taken in its use. The data in this SDS relate only to the specific material designated herein. We do not assume liability for the use of, or reliance on this information, nor do we guarantee its accuracy or completeness.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of ITW Polymers Sealants North America. The data on this sheet relates only to the specific material designated herein. ITW Polymers Sealants North America assumes no legal responsibility for use or reliance upon these data.